

# SAFETY DATA SHEET

G-FIX EPOXY HARDENER

Page: 1

Compilation date: 08/07/2017

Revision No: 1

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** G-FIX EPOXY HARDENER

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** CURING AGENT

### 1.3. Details of the supplier of the safety data sheet

**Company name:** Automotive Bodyfillers Ltd

Unit 4, Millbuck Way

Springvale Industrial Estate

Sandbach

Cheshire

CW11 3HT

**Tel:** 01270 766685

**Fax:** 01270 766685

**Email:** enquiries@resin-supplies.co.uk

**1.4. Emergency telephone number** 01270 766685 Mon-Fri 9am-5pm only

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1A: H317; Repr. 2: H361fd; Aquatic Chronic 1: H410; -: EUH071

**Most important adverse effects:** Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility. Suspected of damaging the unborn child. Very toxic to aquatic life with long lasting effects. Corrosive to the respiratory tract.

### 2.2. Label elements

**Label elements:**

**Hazard statements:** H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H361fd: Suspected of damaging fertility. Suspected of damaging the unborn child.

H410: Very toxic to aquatic life with long lasting effects.

EUH071: Corrosive to the respiratory tract.

**Signal words:** Danger

**Hazard pictograms:** GHS05: Corrosion

[cont...]

# SAFETY DATA SHEET

## G-FIX EPOXY HARDENER

Page: 2

GHS09: Environmental

GHS08: Health hazard

GHS07: Exclamation mark



**Precautionary statements:** P201: Obtain special instructions before use.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P281: Use personal protective equipment as required.  
P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310: Immediately call a POISON CENTER/doctor/.

### 2.3. Other hazards

**Other hazards:** Components of the product may affect the nervous system. May cause sensitisation by skin contact. Severe respiratory irritant. Severe skin irritant.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### BENZYL ALCOHOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-859-9	100-51-6	-	Acute Tox. 4: H332; Acute Tox. 4: H302	10-30%

##### 4-TERT-BUTYLPHENOL

202-679-0	98-54-4	-	Repr. 2: H361f; Skin Irrit. 2: H315; Eye Dam. 1: H318	10-30%
-----------	---------	---	---	--------

##### M-PHENYLENEBIS(METHYLAMINE)

216-032-5	1477-55-0	-	-	10-30%
-----------	-----------	---	---	--------

##### TRIMETHYLHEXANE-1,6-DIAMINE

247-134-8	25620-58-0	-	-	1-10%
-----------	------------	---	---	-------

[cont...]

# SAFETY DATA SHEET

G-FIX EPOXY HARDENER

Page: 3

NONYLPHENOL

246-672-0	25154-52-3	-	Repr. 2: H361fd; Acute Tox. 4: H302; Skin Corr. 1B: H314; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	10-30%
-----------	------------	---	--	--------

**Contains:** POLYAMINE ADDUCT

## Section 4: First aid measures

### 4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning. NOTE TO PHYSICIANS: Application of corticosteroid cream has been effective in treating skin irritation.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** If conscious, give half a litre of water to drink immediately. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

### 4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** If absorbed through the skin, may cause central nervous system effects, such as headache, nausea, dizziness, confusion, breathing difficulties.
- Eye contact:** Corneal edema can cause the perception of "blue haze" or "fog" around lights, although this is a temporary effect and has no known residual effect. Product vapor can cause glaucopsia (corneal edema) when absorbed into the tissue of the eye from the atmosphere.
- Ingestion:** May cause central nervous system effects, such as headache, nausea, vomiting, abdominal pain, dizziness, confusion, breathing difficulties. Severe cases of overexposure can result in respiratory failure.
- Inhalation:** Harmful if inhaled and may cause delayed lung injury. May cause central nervous system effects, such as headache, nausea, dizziness, confusion or breathing difficulties. Severe cases of overexposure can result in respiratory failure. May cause nose, throat and lung irritation. Inhalation of vapors and/or aerosols in high concentration may cause irritation of respiratory system.

[cont...]

# SAFETY DATA SHEET

G-FIX EPOXY HARDENER

Page: 4

## 4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Dry sand or limestone.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** May generate ammonia gas. May generate toxic nitrogen oxide gases. Use of water may result in the formation of very toxic aqueous solutions. Do not allow run-off from fire fighting to enter drains or water courses. May generate toxic, irritating or flammable combustion products. Incomplete combustion may form carbon monoxide. Ammonia gas may be liberated at high temperatures. In case of incomplete combustion an increased formation of oxides of nitrogen (NOx) is to be expected. May generate carbon monoxide and ammonia gas. A sudden reaction and fire may result if product is mixed with an oxidizing agent. Personnel in vicinity and downwind should be evacuated.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear protective clothing to prevent contact with skin and eyes. Wear self-contained breathing apparatus. A face shield should be worn. Retain expended liquids from fire fighting for later disposal.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Use self-contained breathing apparatus and chemically protective clothing. Wear suitable protective clothing, gloves and eye/face protection. Evacuate the area immediately. Open enclosed spaces to outside atmosphere.

### 6.2. Environmental precautions

**Environmental precautions:** Contain the spillage using bunding. Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Approach suspected leak areas with caution. Place in appropriate chemical waste container. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Clean up personnel must be equipped with self contained breathing apparatus and butyl rubber protective clothing. Refer to section 13 of SDS for suitable method of disposal.

### 6.4. Reference to other sections

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Do not use sodium nitrite or other nitrosating agents in formulations containing this

[cont...]

# SAFETY DATA SHEET

## G-FIX EPOXY HARDENER

Page: 5

product. Suspected cancer causing nitrosamines could be formed. Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Avoid breathing vapors and/or aerosols. Avoid contact with eyes. Ensure there is sufficient ventilation of the area. Avoid contact with eyes or skin. Use only in well-ventilated areas. Use personal protective equipment. Do not eat, drink or smoke.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Do not store near acids. Keep container tightly closed. Store in a cool, well ventilated area. Do not store in reactive metal containers. Keep from freezing.

**Suitable packaging:** Do not store in reactive metal containers.

### 7.3. Specific end use(s)

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Provide readily accessible eye wash stations and safety showers. Provide natural or explosive-proof ventilation adequate to ensure concentrations are kept below exposure limits.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Neoprene gloves. PVC gloves. Butyl gloves. Nitrile gloves. Impermeable gloves. The breakthrough time of the selected gloves(s) must be greater than the intended use period.

**Skin protection:** Protective clothing with elasticated cuffs and closed neck. Discard contaminated leather articles. Provide readily accessible eye wash stations and safety showers. Wash at the end of each workshift and before eating, smoking or using the toilet.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Pale yellow

**Odour:** Ammoniacal

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** <0.1 g/l

**Boiling point/range°C:** >200.00

**Flash point°C:** >100

**Autoflammability°C:** No data

**Melting point/range°C:** No data

**Part.coeff. n-octanol/water:** No data

[cont...]

# SAFETY DATA SHEET

G-FIX EPOXY HARDENER

Page: 6

Relative density: 0.99

Vapour pressure: 10.34mmHg

pH: Alkaline

## 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

### 10.5. Incompatible materials

**Materials to avoid:** Reactive metals (e.g. sodium, calcium, zinc etc) Materials reactive with hydroxyl compounds. CAUTION ! N-Nitrosamines, many of which are known to be potent carcinogens, may be formed when the product comes in contact with nitrous acid, nitrites or atmospheres with high nitrous oxide concentrations. Mineral acids. Organic Acids (i.e. acetic acid, citric acid etc) Sodium Hypochlorite. Product slowly corrodes copper, aluminium, zinc and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. Oxidizing agents.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In case of fire hazardous decomposition products may be produced such as: Carbon Monoxide - Carbon Dioxide(CO<sup>2</sup>)-Nitric Acid - Ammonia - Nitrogen Oxides(NO<sub>x</sub>)-Nitrogen Oxide can react with water vapors to form corrosive nitric acid. - Aldehydes. Nitrosamine. Flammable hydrocarbon fragments (e.g. acetylene).

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Toxicity values:

Route	Species	Test	Value	Units
ORL	RAT	LD50	2,951	mg/kg

#### Hazardous ingredients:

##### BENZYL ALCOHOL

IVN	RAT	LD50	53	mg/kg
-----	-----	------	----	-------

[cont...]

# SAFETY DATA SHEET

## G-FIX EPOXY HARDENER

Page: 7

ORL	MUS	LD50	1360	mg/kg
ORL	RAT	LD50	1230	mg/kg

### NONYLPHENOL

ORL	MUS	LD50	1231	mg/kg
ORL	RAT	LD50	580	mg/kg

### Symptoms / routes of exposure

**Skin contact:** If absorbed through the skin, may cause central nervous system effects, such as headache, nausea, dizziness, confusion, breathing difficulties.

**Eye contact:** Corneal edema can cause the perception of "blue haze" or "fog" around lights, although this is a temporary effect and has no known residual effect. Product vapor can cause glaucopsia (corneal edema) when absorbed into the tissue of the eye from the atmosphere.

**Ingestion:** May cause central nervous system effects, such as headache, nausea, vomiting, abdominal pain, dizziness, confusion, breathing difficulties. Severe cases of overexposure can result in respiratory failure.

**Inhalation:** Harmful if inhaled and may cause delayed lung injury. May cause central nervous system effects, such as headache, nausea, dizziness, confusion or breathing difficulties. Severe cases of overexposure can result in respiratory failure. May cause nose, throat and lung irritation. Inhalation of vapors and/or aerosols in high concentration may cause irritation of respiratory system.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data is available on the product itself. Bioaccumulation - components:- Benzyl alcohol - Low bioaccumulation potential. Nonylphenol - Moderate bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** No data available.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

[cont...]

# SAFETY DATA SHEET

G-FIX EPOXY HARDENER

Page: 8

## 12.6. Other adverse effects

**Other adverse effects:** Aquatic toxicity: No data is available on the product itself.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Recovery operations:** Waste from residues/unused : Contact supplier if guidance is required.

**Disposal of packaging:** Dispose of container and unused contents in accordance with federal, state and local requirements

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN2735

### 14.2. UN proper shipping name

**Shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S., (BENZENE-1,3-DIMETHANEAMINE (MXDA), TRIMETHYLHEXANE-1,5-DIAMINE )

### 14.3. Transport hazard class(es)

**Transport class:** 8

### 14.4. Packing group

**Packing group:** II

### 14.5. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** Yes

### 14.6. Special precautions for user

**Tunnel code:** (E)

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** USA - TSCA : Included on Inventory

EU - EINECS : Included on EINECS inventory or polymer substance, monomers included on EINECS inventory or no longer polymer.

Canada - DSL : Included on Inventory

Australia - AICS : Included on Inventory.

[cont...]



## SAFETY DATA SHEET

### G-FIX EPOXY HARDENER

Page: 9

Japan - ENCS : Included on Inventory.

South Korea - ECL : Included on Inventory.

China - SEPA : Included on Inventory.

Philippines - PICCS : Included on Inventory.

**Phrases used in s.2 and s.3:** EUH071: Corrosive to the respiratory tract.

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H332: Harmful if inhaled.

H361f: Suspected of damaging fertility.

H361fd: Suspected of damaging fertility. Suspected of damaging the unborn child.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.